## Litho Panel Discussion Summary

- 1. Immersion will most likely carry litho to 45nm hp
- 2. EUV is most likely required for 32nm hp
- 3. First introduction of EUV into mfg: in 2009 (Van den hove, Abe, Arnold). Infrastructure is a challenge (Arnold)
  - NAND Flash has the most aggressive litho roadmap: 32nm hp in 2009 (Arnold)
- Litho cost per bit continues to decreases → very good news (Lercel)
- 5. Optical mask becoming increasingly complex leading to high cost (Hayashi), prohibitive for low volume
- 6. Litho Cost: if target met, EUV offers best cost-per-bit solution for 45nm hp, 32nm hp node and beyond (Lercel, Abe, Hector)
- 7. Litho Performance: when available, EUV offers high k1 process (Abe, Hector, Lercel)
- 8. Collaboration to develop infrastructure needed

# Key Challenges

## Hyper NA Immersion

- Complex RET's, OPC's, data volume, low k1
  - Mask wrier, inspection and repair tools
- Hyper NA requires high index fluid and resist and lens materials

#### EUV

- Mask blank defectivity
- Reticle handling (no pellicle)
- Development cost and readiness for 2009 introduction

### Mask:

Mask cost due to complexity (OPC, RET, Data volume, etc.)